

Development

Code Server (Vistual Studio Code)

- <https://docs.linuxserver.io/images/docker-code-server>

```
docker run -d \  
  --name=code-server \  
  -e PUID=1000 \  
  -e PGID=1000 \  
  -e TZ=Europe/Vienna \  
  -e PASSWORD=password `#optional` \  
  -e HASHED_PASSWORD= `#optional` \  
  -e SUDO_PASSWORD=password `#optional` \  
  -e SUDO_PASSWORD_HASH= `#optional` \  
  -e PROXY_DOMAIN=code-server.my.domain `#optional` \  
  -e DEFAULT_WORKSPACE=/config/workspace `#optional` \  
  -p 8443:8443 \  
  -v /path/to/appdata/config:/config \  
  --restart unless-stopped \  
  lscr.io/linuxserver/code-server:latest
```

- minimal cli command:

```
docker run -d \  
  --name=code-server \  
  -e PUID=1000 \  
  -e PGID=1000 \  
  -e TZ=Europe/Vienna \  
  -e PASSWORD=password \  
  -e SUDO_PASSWORD=password \  
  -e PROXY_DOMAIN=code.vps2.draab.at \  
  -p 8443:8443 \  
  -v ~/code-server/config:/config \  
  --restart unless-stopped \  
  lscr.io/linuxserver/code-server:latest
```

Hoppscotch Api client

<https://github.com/hoppscotch/hoppscotch>

GlitchTip

<https://glitchtip.com/>

<https://glitchtip.com/assets/docker-compose.sample.yml>

MySql

phpmyadmin

docker compose snippet:

```
phpmyadmin:
  image: 'phpmyadmin:latest'
  ports:
    - 8080:80
  networks:
    - <NETWORK>
  environment:
    - PMA_ARBITRARY=1
```

Mail

Mailcatcher

<https://mailcatcher.me/>

```
sudo docker run -d --rm -p 1025:1025 -p 1080:1080 --name mailcatcher sj26/mailcatcher
```

- `localhost:1025` config for mail server
- `http://localhost:1080` to view mails tried to sent

Mailhog

[Github](#)

```
sudo docker run -d --rm -p 1025:1025 -p 8025:8025 --name mailhog mailhog/mailhog:latest
```

go to `http://localhost:8025`

MailPit

[Homepage](#)

remove container after it stops:

```
docker run -d \  
--rm \  
--name=mailpit \  
-p 8025:8025 \  
-p 1025:1025 \  
axllent/mailpit
```

keep container running

```
docker run -d \  
--restart unless-stopped \  
--name=mailpit \  
-p 8025:8025 \  
-p 1025:1025 \  
axllent/mailpit
```

docker compose:

```
service:  
  
    mailpit:
```

```
image: 'axllent/mailpit:latest'
```

```
ports:
```

```
  - '${FORWARD_MAILPIT_PORT:-1025}:1025'
```

```
  - '${FORWARD_MAILPIT_DASHBOARD_PORT:-8025}:8025'
```

```
networks:
```

```
  - <NETWORK>
```

Created 2022-10-27 12:34:49 UTC by Daniel Raab

Updated 2024-10-28 11:52:53 UTC by Daniel Raab